

HIGH SPEED TILTING OPEN POCKET WASHING MACHINE



AVAILABLE IN 200KG

Our high speed tilting open pocket washing machine provides high quality processing results on a wide range of materials, in demanding conditions.

They are designed to meet the demands of:

- Hospitals
- Prisons
- Industrial Laundries
- Hotels

FEATURES AND BENEFITS

- User friendly touch screen operator controls
- Adaptable PLC programs for greater efficiency and flexibility
- Accurate control of water and supplies usage
- Variable wash and spin speeds minimizing programme times
- Reduction of pressure creasing through programmable extract speed
- Tested stainless steel elements ensuring long hygienic life performance
- Compact design and easy access for maintenance
- Manufactured to ISO 9001-2015 Quality Standard
- Meets all UK and EU safety legislation



HIGH SPEED TILTING OPEN POCKET WASHING MACHINE

MODEL	UNITS	200kgs
Capacity	Kgs/lbs	200 / 440
Size - length	mm	2550
Size - width	mm	2250
Size - height	mm	2240
Drum diameter	mm	∅1600
Drum length	mm	1100
Drum volume	m ³	2.212
Door diameter	mm	760
Loading height	mm	920
Variable wash speed	rpm	5–30
Balance speed	rpm	53
Extract speeds	rpm	290–650
'G' Factor - extract	G	378
Motor size	Kw	30
Electrical power	V/Ph/Hz	440/3/50
Power consumption	Kw/Cycle	2.6
Electrical cable (<20m run length)	mm ²	16 x 4 line
Steam inlet size	BSP	1 1/2"
Steam pressure	Bar	4–5 (5 max)
Water inlet size	mm	2 1/2"
Water pressure	Bar	2–3 (3 max)
Air inlet size	mm	10
Air pressure	Bar	4–5 (5 max)
Drain outlet diameter	mm	2 x ∅114
Net weight	Kgs	7400
Shipping weight	Kgs	7950
Shipping volume	Cu. M	14.14

Cherry Tree reserve the right to amend specification without notice.

NOTE: Model tilts forward only.



Email - sales@cherrytreemachines.co.uk
 Call - 01254 671155
 Visit - cherrytreemachines.co.uk

