

HIGH SPEED OPEN POCKET WASHING MACHINES

AVAILABLE IN 25KG, 50KG & 100KG

Our range of high speed open pocket washing machines provide high quality processing results on a wide range of materials, in demanding conditions.

They are designed to meet the demands of:

- Hospitals
- Prisons
- Industrial Laundries
- Hotels

FEATURES AND BENEFITS

- User friendly touch screen operator controls
- Adaptable PLC programs for greater efficiency and flexibility
- Accurate control of water and supplies usage
- Variable wash and spin speeds minimizing programme times
- Reduction of pressure creasing through programmable extract speed
- Tested stainless steel elements ensuring long hygienic life performance
- Available in electric or steam heat
- Compact design and easy access for maintenance
- Manufactured to ISO 9001-2015 Quality Standard
- Meets all UK and EU safety legislation



HIGH SPEED OPEN POCKET WASHING MACHINES

MODEL	UNITS	25kgs	50kgs	100kgs
Capacity	Kgs/lbs	25 / 55	50 / 110	100 / 220
Size - length	mm	1285	1440	1880
Size - width	mm	1150	1320	1680
Size - height	mm	1540	1705	1960
Drum diameter	mm	ø880	ø990	ø1240
Drum length	mm	496	710	910
Drum volume	m ³	0.30	0.50	1.014
Door diameter	mm	ø520	ø520	ø570
Loading height	mm	675	750	860
Variable wash speed	rpm	5 - 75	5 - 50	5 - 40
Balance speed	rpm	60	60	60
Extract speeds	rpm	430 - 810	375 - 800	325 - 700
'G' Factor - extract	G	323	354	340
Motor size	Kw	3	5.5	7.5
Electrical power	V/Ph/Hz	400V/ 3Ph/ 50	400V/ 3Ph/ 50	400V/ 3Ph/ 50
Available heating method		Electric/Steam	Electric/Steam	Steam
Power consumption steam heated	Kw/cycle	0.8	1.0	1.8
Power consumption electric heated	Kw/cycle	17	30	-
Electrical cable - steam heated (<20m run length)	mm ²	6 x 4 line	6 x 4 line	10 x 4 line
Electrical cable - electric heated (<20m run length)	mm ²	10 x 4 line	16 x 4 line	-
Steam inlet size - steam heated	BSP	¾"	1"	1 ½"
Steam pressure - steam heated	Bar	4-5 (5 max)	4-5 (5 max)	4-5 (5 max)
Water inlet size	BSP	1"	1 ½"	2"
Water pressure	Bar	2-3 (3 max)	2-3 (3 max)	2-3 (3 max)
Air inlet size	mm	8	8	8
Air pressure	Bar	4-5 (5 max)	4-5 (5 max)	4-5 (5 max)
Drain outlet diameter	mm	1 x ø80	2 x ø80	2 x ø114
Net weight	Kgs	1200	1800	3200
Shipping weight	Kgs	1280	1980	3520
Shipping volume	Cu. M	1.78	3.63	6.75

Cherry Tree reserve the right to amend specification without notice.



Email - sales@cherrytreemachines.co.uk

Call - 01254 671155

Visit - cherrytreemachines.co.uk

